Re-packing the DSM Safety Banner

- 1. Allow the DSM safety banner to freely hang from the carrier.
- Insure that the bungee cord is free of kinks and flows through the grommets holes without kinks or twists, place the corners of the DSM Safety Banner together.





- 3. Insure that the "grab handle" is in the midposition of the DSM Safety banner.
- 4. Grab the DSM Safety banner (about where the "I" in police) and fold banner in half, towards the user.





- 5. Now using your fingers begin to roll the DSM Safety banner towards the user.
- 6. When this is approx. 5-6" left in the banner to roll, take the "banner grab handle" and fold it 90 degrees from the banner.





 Continue to roll the banner (this should leave the grab handle sitting on "top end" of the rolled banner)





- 8. Insert the "lower end" (opposite of the grab handle) of the rolled banner into the carrier, insuring that the grab handle is on top of the banner when sitting in the carrier.
- 9. Fold the flap of the carrier over the banner to close making sure that no part of the banner is visible from the carrier. (This carrier was specially designed to totally conceal the DSM Safety Banner and appear as an everyday cell phone holder).





Alternative Deployment method

- 1.Open pouch
- 2. Identify and grab "the grab handle" (vinyl tube surrounding the DSM Safety banner) straight up, allowing the banner to unravel.
- 3. Allowing some slack in the banner, bring the palm side of your hand to the top of your head and feed your head through the loophole in the banner.
- 4. Release the banner allowing it to rest on the opposite shoulder then place your support arm/hand through the opening of the banner.
- 5. Run hand over the banner to insure that it is readable.